Integration of high productivity and high quality machining



E

YASDA PRECISION CENTER



5-Axis Machining Center

Reliability of machining at work shops,in-house built tilting rotary table Yasda preload self-adjusting spindle,versatile machining capability





Market is demanding both high speed machining and high production capacity The new 5-axis machining center is integrating highly efficient and high quality machining performance of YASDA into those features at a higher dimension



5-axis

Integration of unprecedented high productivity and stable machining accuracy

PX30i is capable of high volume and high-mix production inheriting the DNA of the YBM series which demonstrate high performance in 5-axis machining of complicated shape components.





ATC tool capacity Max 314 Large capacity automatic tool changer (ATC) prepared for long-time continuous machining and large volume production



Number of pallets 33 sets Equipped with a stocker capable of storing 33 pallets



Operating system YASDA's unique operating system connecting operator and machine

Symmetrical construction realizes high speed high efficiency and high quality machining

Symmetrical construction

Basic construction which has been designed through complete FEM analysis ensures high rigidity, and symmetric cast iron frame exerts maximum effect on minimizing thermal deformation. This achieves high reliability in stable precision-machining and highly accurate positioning machining.

Positioning accuracy (measured value)

ISO 230-2(1988)			unit(mm)			
A A	Х	Y	Z			
Accuracy: A	0.0026	0.0021	0.0027			
ISO 230-2(2014) unit(mm)						
	Х	Y	Z			
Accuracy: A	0.0023	0.0014	0.0021			
	Х	Y	Z			
Repeatability : R	0.0008	0.0006	0.0007			



The highly rigid integrated portal structure dominates the field of high precision and heavy-duty cutting

Equipped with a highly rigid and high-precision B/C-axis tilting rotary table unit is mounted on Y-axis, minimizing weight differences in movable bodies of each axis, and setting the heavy movable bodies to lower center of gravity.

The machine body adopts a bridge type thermally symmetrical structure with less thermal displacement. A single-piece structure (column and top beam) made of high grade cast-iron further improves rigidity. With a highly rigid feed drive system adopting large diameter ball screws and high speed interpolation control function, high-speed and high-precision machining is achieved.

Circulation of coolant in the bearings and support jackets for linear axis prepared for high-speed machining.

B-axis Driven by DD (direct drive) motor

High rigidity
Supported at
2 points

C-axis Driven by DD motor

High precision linear roller guides are mounted at the straightness of 2μ m or less.

YASDA's classic preload self-adjusting spindle

Both heavy-duty cutting in a low-speed range and high-precision rotation in a high-speed range with low heat generation are realized

By the unique mechanism of the preload self-adjusting spindle that applies a large preload at low-speed rotation while preload decreases in accordance with the amount of heat generation of the spindle bearing at high-speed rotation, heavy-duty cutting, high-speed machining of highly hardened steel and high precision machining with helix end mill that generates a thrust-reversing force are realized.

Cooling oil is circulated in the spindle and spindle motor, which generate the most heat in the machine.



Spindle motor

A two coil type spindle motor is employed for realizing both high speed rotation and low speed rotation at high torque drive. In addition, the slim nose shape ensures good accessibility to work pieces.

Direct drive system

The spindle and the spindle drive motor are connected co-axially by a coupling in order to achieve high precision rotation of the spindle throughout the full speed range of the spindle.



Newly designed combination table with higher reliability

B/C-axis direct drive table

The tilting rotary table has been newly developed to increase reliability and eliminate redundancy. It is driven by direct drive motors to achieve rapid and accurate positioning as well as smooth interpolation motion. The cradle where the pallet is mounted is supported by the large diameter rotor bearing on the motor side and by a high rigid bearing on the other side.

Coolant is circulated in the B/C-axis motors and bearings to minimize the impact of thermal displacement. The pallet clamp system employs a highly reliable air release method. Strong clamping force further increases cutting capacity.







System 3R Matrix185

Outstanding accuracy

This machine achieved 3.10µm of circularity (measured value) in a tilted cone machining test according to NAS979 standard, which is commonly used for simultaneous 5-axis machining accuracy.





Automatic tool changer (ATC) promises reliable operability

Max 314 tools storage prepared for long-time continuous machining and large volume production

ATC

Designed for ø80mm standard tool and bigger tool up to ø150mm.



Tool loading position

sition Ready/return position

Tool dimensions





ATC operation touch panel

Intuitive and smart operation is realized by easy-to-understand icons, button arrangement and high visibility layout. This touch panel allows one-touch secure operation for tool storage, ATC manual operation, recovery function at the time of trouble, displaying tool information, etc., thus reducing stress on the operator.





Unprecedented long-time unmanned schedule operation is realized

Pallet stocker which can store 33 sets of work pieces

Pallets are automatically changed according to the machining schedule, thus long-time unmanned schedule operation is realized.

All axes in the handling system are driven by servo motors ensuring high speed and exact handling operations.



Improvement in workability

Machine and PLS operations, and work setup positions are arranged closely to each other to improve workability. Visibility is significantly improved by the 15-inch operation panel.





Operator-friendly design

The position of the upper surface of the pallet is set to 1,085mm from the machine floor. The center of pallet to the operator door is set to 610mm, allowing the operator an easy access to tools and the workpiece.



Original operation system

The interface that connects man to machine "OpeNe" (Operator+Machine)

"YASDA OpeNe" is a YASDA's original system which widely supports operation of the machine such as machine status check, customization etc.

OpeNe

STANDARD version

This is a basic operation function containing total auxiliary screen, customization functions etc., to meet various customer's needs.

	20	25 25 13.1
4 9 14	19	24
3 8 13	18	23 WAIT RETURN
2 7 12	17	22 27 31
1 <u>6</u> 11	16	21 . 28 . 30
1/0	FORM	

Enhanced work management function

This function enables detailed settings such as assignment of programs, pallets, machining order, etc.

NC BOTTERY		BUTTERY OASE NO. 1			
BATTERY EXCHANGE DATE	83/85/2815	INTERV EXCHANCE INTE	83-86-2815		
NEXT EXCHANGE DATE	813/86/2816	HEXT EXCHANGE DITE	83/86/2016		

Battery maintenance function

The battery change time is indicated with a message to prevent trouble due to end of battery life and to reduce maintenance work.

• Other: Customization function, total auxiliary screen etc.

OpeNe

EXTENDED version

Ope

Operator + Machine

In addition to the STANDARD function, useful functions for assisting high productivity and automation are available as options.

HD.	1008.	HEL.	MIT.	LIFE YYPE	COUNT	HINK	HOTICE LIFE	LIFE
	1901	101	1	TIME	3:45:00	5:00:00	0:10:00	EMARLE
1944	1982	182	1	TIME	8:57:80	3:00:00	8:20:88	ENHIBLE
183	1003	183		71HE	7:26:00	10:00:00	1:00:00	DISELE
1041	1004	184		TIME	2100:00	2:00:00	0130(80	OVER
1903	1600	10.0		COUNT	20	500	10	EMPORTE
105	1096	100	2	TIME	11:00:00	2:00:00	0:00:00	EMARKE
107	1002	107	102	TINE	0:00:00	d:00:00	0:00:00	EMODLE
188	1068	188	2	TINE	4:03:00	7:88:88	0:00:00	ENHILE
1000	1009	109	2	TIME	2:35:00	3:00:00	81 15:80	DOM: NO
120	1010	110	2	TINE	0:00:00	4100100	0:00:00	DISIL
111	3011	111		1116	3:12:00	5:00:00	0130100	DISIL
112	1012	112		11HE	2145-88	3:00:00	0130180	NOTICE
113	1013	113		TIME	0:99:00	2:00:00	0:00:00	CHARLE.
114	1014	214		COUNT	35	100	10	EMSBLE
115	1015	115	1.50	TINE	0:00:00	3:00:90	0:30:80	EMARLE

Tool management function

Enhanced tool management function such as tool life and spare tool life is included.

-	SCUICE HAIN FO SUB FOL PROGRAM	LDER DEN	CAC_JED-UDER PATHI SUBJECK ELLEND				Status Hexce	
T	TUOL HD.	POT	LEDISTIC	LEHGTH	REALUS GEOM	RIND THES	LIFE]
123456709	18801 18812 18812 1884 1884 1885 1886 18872 2880 2880 2880	181 182 103 184 185 186 187 128	362, 8743 458, 8247 298, 5434 338, 0664 241, 1977 199, 7666 365, 6500 325, 0442	-0. 8309 0. 8809 -0. 0045 -0. 0045 -0. 0045 -0. 0045 -0. 0045 -0. 0000 -0. 0000 0. 0000	32, 9855 8, 0080 35, 3600 8, 0080 19, 9509 8, 0886 27, 9400 8, 0680	0, 909 0, 909 0, 909 0, 909 -0, 125 0, 909 -0, 901 0, 999		

Stored tool confirmation function

This function confirms status of all tools used before machining, and determines whether they can be used or not. This allows for flexible production by assigning priority to machinable pallets.

• Other: Production management function etc.



High functionality and on-machine measurement options

Options to support sophisticated centering coordinate setting and calibration

Measurement and calibration application software to realize even more sophisticated and highly accurate 5-axis machining are available as options. The user-friendly interfaces are integrated in the OpeNe screen.



Measurement application

"Ez-Me"&"Ez-Me Pro"

(option)

The measurement application software "Ez-Me" and "Ez-Me Pro", using the manual pulse generator, are available as options. A wide variety of measurements from centering to confirmation after machining are done on the machine by intuitive operations. "Ez-Me Pro" offers a number of measurement patterns including angle measurement and calibration of rotation axis, calculation of peak from derived angle, etc. Thus it is very useful for sophisticated centering and measurement.

Machine calibration application

(option)

"Ez-CAL" & "i-CAL"

Ez-CAL

This function measures the length of the automatic touch probe in the Z-axis direction and calibrates the displacement in distance between table and spindle due to room temperature change, etc., and significantly increases the reliability of measurement.

One-touch calibration

i-CAL

This function calibrates the center coordinate of the tilting axis (B-axis) and rotation axis (C-axis). For tool center point control (TCP) and index machining (TWP), this function is essential for high precision 5-axis machining as each axis of the machine moves according to this center coordinate.

This function allows one-touch operation on the OpeNe screen for Ez-CAL, i-CAL, normal automatic centering and calibration of tool measurement device.

Ez-Me, Ez-Me Pro: Subject to the machine with auto measuring probe Renishaw OMP400. Ez-CAL: Subject to the machine with a non-contact type tool measurement device. i-CAL: Subject to the machine with an auto measuring probe.

1. Specifications of	base machine				
1) Travel	X-axis travel		680mm		
	Y-axis travel		400mm		
	Z-axis travel		500mm		
	B-axis travel		−125.0°~+65.0°		
	Distance from table surface to spindle nose face ($B=0^{\circ}$)		120~620mm		
	Distance from C-axis center to spindle no:	se face (B=90°)	90~590mm		
	Least input increment		0.0001mm		
2) Rotary table	Table working surface		<i>ф</i> 185mm		
(B / C axis)	Table loading capacity/moment	80N.m			
	Table surface configuration	13-M10 tap			
	Maximum pivot diameter of work	ϕ 400mm (with limitation)			
	Maximum work height	315mm (with limitation)			
	Least input increment	0.0001°			
3) Spindle	Spindle type	SA40-20000-18.5 (Preload self-adjusting spindle)			
	Spindle speed range		100~20,000min ⁻¹		
	Spindle drive motor	AC15 / 18.5kW (Continuous/30min)			
	Spindle taper hole		7 / 24 Taper No.40(HSK-A63 option)		
4) Feed rate	Rapid traverse rate		(X-,Y-,Z- axis) 60,000mm/min (B-axis) 75min ⁻¹ (C-axis) 125min ⁻¹		
	Cutting feed rate		(X-,Y-,Z- axis) 20,000mm/min (B-axis) Max50min ⁻¹ (C-axis) Max50min ⁻¹		
	Least input increment	0.0001mm (deg)			
5) Automatic tool chang	ger		314 tools (Max)		
6) Maximum tool diame	eter / length / mass		¢150mm / 300mm / 10kg		
7) Automatic pallet cha	nger		Pallet number 33 faces		
8) Pallet chucking devic	е		System 3R: Matrix 185 With pallet seating check function		
9) Mass of base machin	e		Approx. 19,000kg		
10) Electric power capa	acity		60kVA		
11) NC unit			FANUC 31i-B5 15 inch monitor		
2. Optional equipm	ent				
1) Signal tower (Multilay	ver signal lamp) 7)	Tool length / ra	adius compensation and tool breakage sensor		
2) Spindle center throug	gh air coolant 8)	Automatic me	easuring system		
3) Spindle center throug	gh flood coolant 9)	9) High-speed machining function (YASDA HAS-3 system)			

- 9) High-speed machining function (YASDA HAS-3 system)
- 10) Weekly timer
- 11) Thermal displacement compensation for spindle

6) Automatic tool length compensation and tool breakage sensor

4) Cutting fluid temperature control unit

9 YASDA PRECISION CENTER PX30i

5) Mist collector

3. CNC Options	
1) Part program storage	512KB·1MB·2MB·4MB·8MB
2) Extensional number of registerable programs	250.500.1,000.2,000.4,000
3) Background editing	
4) Helical interpolation	G02•G03
5) Conical / spiral interpolation	n G02·G03 (Helical interpolation is required)
6) Inch / Metric conversion	G20•G21
7) Scaling	G50•G51
8) Coordinate system rotation	G68•G69
9) Programmable mirror image	G50.1•G51.1
10) Rigid tap	M29 (G84·G74)
11) Optional block skip	Total : 9

12) Tool offset pairs	499sets	• 999sets
13) Custom macro common v	variable T	otal : 600
14) Addition of workpiece co	ordinate 48sets	• 300sets
15) Tool management		
16) Normal direction control		
17) Cs contouring control		
18) Three-dimensional coordi	nate conversion	i68 • G69
19) Inverse time feed		G93
20) Ethernet function	FOCAS2 / Etherne	t function
21) Data server function	Fast da Capacity 1GB	ata server, ,2GB,4GB

OUTLINE



DIMENSION



YASDA PRECISION TOOLS K.K.

www.yasda.co.jp

Main Office & Factory:

1160Hamanaka,Satosho-cho,Okayama,719-0303,Japan PHONE: +81/865-64-2511 FAX:+81/865-64-4535

Representative Office:

Schiessstr. 35, D-40549 Düsseldorf Germany PHONE: +49/211-598937-40 FAX: +49/211-598937-50

YASDA PRECISION AMERICA CORPORATION

62 North Lively Boulevard, Elk Grove Village, IL 60007, U.S.A. PHONE: +1/847-439-0201 FAX: +1/847-439-0260

YASDA PRECISION TOOLS (SHANGHAI)

Room. 1001 Orient International Plaza Part(C), No.85 Lou Shan Guan Road, Shanghai, 200336, China PHONE: +86/21-62700955 FAX: +86/21-62700970

Dongguan Office:

5A Xingye Building, No.89.Lianfeng Road, Changan Town, Dongguan City, Guangdong, 523850, China PHONE: +86/769-82283036 FAX: +86/769-82283086

*Export of the products and associated software, and related services are subject to prior approval of the Japanese government according to "Foreign Exchange and Foreign Trade Law".