

D-CUBES

The Art of Economy

Wire-cut EDM

Power for Precision **MV-R CONNECT**



42 model series since 1964.

An assurance of innovation and dependability.

Mitsubishi Electric

Functions and machine concept

Machine concept	Э
Design 1	1
Tubular Shaft Motor 13	3
Crash Protection System	5
Wire threading	7
Generator technology	9
Precise Finish Circuit	1
Corehold 22	3

Dialogue-assisted navigation	25
Professional mode	27
Intelligent user guidance	29
Job scheduler	31
Monitoring	33
New intelligence	35



Profitability / Options / Services

Maintenance-friendliness	39
Profitability	41
Optional extras and non-standard materials	45
Automation	49

Examples of applications	51
Service	53
Training	55



3

	Kev	data .																								57	
--	-----	--------	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	----	--

Technical data	6	51







If you've got grand designs,

you need someone strong you can count on.





Since 1970, a growing number of European companies have therefore been turning to high-performance EDM machines from world market leader Mitsubishi Electric.

Only by producing components in-house is it possible to tailor them perfectly to the intended task. Mitsubishi Electric resorts to its own controls, semiconductors, motors and other items, which are adapted in detail to all requirements. The only thing you notice is that it works and often for many decades after purchase.

If you want to invest soundly in a durable EDM machine, choose Mitsubishi Electric.

This way I know I'm in good hands. 5





Intuitive operation – for the benefit of the machine operator.

The user interface is child's play to handle – gesture control inclusive. While some choose dialogue-supported user guidance, others opt for professional mode to get off to a speedy start. The control adapts to the user. Continued on page 27



Extra precision and speed thanks to the generator that not only thinks, but also thinks ahead.

If you want to achieve better surface quality with fewer recuts, you need the right blend of mutually adapted technologies. With Precise Finish Circuit, you achieve more precise results faster.

Continued on page 21



An EDM system must help your company to make money.

The MV-R Series cuts expenditure on electricity, wire and filters considerably – so that you can earn more. The machine is designed for decades and has extra-low maintenance needs thanks to intelligent technologies. Continued on page 39



Thrilling technology.

The machine results you expect – in a playful, transparent, efficient and reliable process

These days, the operation of a CNC machine no longer has to be complicated – the dialogue guidance of the CNC helps less experienced machine operators to reliably accomplish their tasks. The transparency of the machining processes on the EDM system and overviews of the state of maintenance and resource consumption are a help with cost analysis and preventive maintenance. The analysis functions thus help to boost efficiency by exploiting capacities and resources better – and boost the proverbial reliability of the EDM systems from Mitsubishi Electric still further.

The speed of light...

... for communication by fibre optics.

The Tubular Shaft Motor with its highly responsive control fully exploits the benefits of high communication speed. No heat, no maintenance and no contact – just extra precision for good. At Mitsubishi Electric, this is known as "Changes for the Better".

Continued on page 13



Wire break point insertion even on thick and interrupted workpieces.

The time-consuming return to the starting point is omitted – and machining continues where it left off, thanks to the highly advanced wire annealing system. Depending on machining conditions, threading can be successfully performed with or without jet stream and even submerged – depending on workpiece thickness.



Continued on page 17





MV2400R Connect – the perfect blend of performance and ergonomics



Ergonomic machine strategy

enabling you to concentrate on the essential.





Intelligent D-CUBES control



Network for productivity



Set-up, programming, maintenance etc. - all the key elements are directly accessible at the front of the machine. The entire wire feed, automatic wire threading and wire guide heads plus the whole workspace are readily accessible - not least thanks to the open design and automatic vertical sliding door.

... simply shifts the future into the present. The user has almost half a metre of user interface to work with, assisted in this by the mouse and the usual computer keyboard. The monitoring of the machining process generates neatly displayed information at a glance and detailed analysis where desired.

All the critical data can be conveniently retrieved through the ERP system. The Controller supplies all relevant operational data for further external use as a standard function. Important interfaces such as Ethernet TCP/IP are of course part of the package.

No more elegant way of mastering difficult tasks. 9

Ingenious drive positioning

If you want extra-smooth axis movements, you have to position the drives right in the centre of the moving weight – so that the superior Tubular Shaft Motor can exploit its full potential. Glass scales right next to the work space are an assurance of maximum precision right from the start.

Tons of solidity cast in steel.

Solid machine body



Durable hardened stainless steel table



The door that simply vanishes...

1



00

The specially selected Meehanite casting ensures durability that can be measured in decades and copes with high workpiece weights day after day. The rugged machine bed takes even the severest punishment in its stride – unlike many a less expensive material. The four-sided table is insensitive to dielectric and sludge for decades. High-grade stainless steel components and the stainless steel work tank ensure dependability and maintenance-freedom. ...so that you have direct access. This saves time and space and makes workpiece set-up that much easier.

The Tubular Shaft Motor converts energy directly into motion, without contact, without maintenance and above all without loss of precision – long-term. Combined with the 400% faster fibre-optic-based control, this superior technology can truly show what it is capable of.

The positioning accuracy even of the large MV2400R is $< +/- 2 \mu m$ over the entire travel path – there's a genuine 12-year manufacturer warranty for this on all Mitsubishi Electric EDM systems. An assurance of top-level durability.

Your company's technological edge has a name: Tubular Shaft Motor – from world market leader Mitsubishi Electric.



Find out more about it here: www.mitsubishi-edm.de/tsm

12-year warranty



MV-R CONNECT

Perfect drive



on positioning accuracy.

Speed of light



No disruptive cogging torque







What was it about conventional drive systems that bothered developers at Mitsubishi Electric? The need for lubrication, the friction and frictional heat, power consumption, backlash, the cogging moment and above all the possible wear. Only a non-contact drive overcomes these drawbacks from the outset and is thus an assurance of better results and enhanced dependability over decades. The Mitsubishi Electric polymer optical fibres have decisive advantages – not only over conventional copper cables, but also over glass fibres. Not only their total resistance to water, but also their high transmission rates combined with minimal space requirements and maximum flexibility are essential for truly progressive EDM systems. The only thing that you as a user notice is the longer service life and enhanced precision. You're surely familiar with the cogging torque manifested by a conventional electric motor. It is precisely this cogging torque that is undesirable, as are variations in torque. The Tubular Shaft Motor – the optimal drive for precision applications like electrical discharge machining.

Non-contact drive = trouble-free long-term drive. 13



Crash Protection System



MV-R CONNECT

already installed.

Crash Protection System in action



The in-built "guardian angel"



Fully automatic





Care, attention and good planning are an assurance of immaculate results, even with the most advanced technology. And should the unexpected nevertheless occur, all the wire-cut EDMs from Mitsubishi Electric come with an in-built "crash protection system". The wire-cut EDM systems from Mitsubishi Electric constantly check current axial forces and thus fully automatically detect potential accidents before they happen. If there is an obstacle in the travel path, this is electronically detected on the basis of the drive's load change during the approach and the control automatically reverses. Better safe than sorry! See for yourself and watch the dependable Crash Protection System from Mitsubishi Electric in action!







Vastly superior. The wire threader for maximum dependability.



Wire break point insertion even on thick and interrupted workpieces



Round diamond guide



Flexibility – when it comes to wire diameter



The time-consuming return to the starting point is omitted - and machining continues where it left off, thanks to the highly advanced wire annealing system. Depending on machining conditions, threading can be successfully performed with or without jet stream and even submerged - depending on workpiece thickness.

Maximum precision and durability ensure the best results in the long run - inclusive of maintenancefriendliness due to a small number of parts and simple design.

Intelligent AT is designed for wire thicknesses of 0.10–0.30 mm, i.e. the right range for more than 95% of all applications. But what if you need thinner wire? No problem. Intelligent AT is optionally available for the 0.05–0.30 mm range as well.



Greater speed and accuracy –



and you save more.

Response time is decisive

An EDM machine that reacts with greater speed and precision achieves better surface quality faster. The new V350 generator has a significantly higher effective clock rate. The voltage is built up faster and with greater precision thanks to reduced capacitance loss. Thanks to faster voltage build-up, spark duration and working voltage can be lowered. All that you will probably notice is higher surface quality and lower power costs.

17% faster multi-pass jobs

0.12 µm surface quality

um RA 0.75

Proven surface qua

New H-FS generator stage





4 cuts of Ra 0.28 µm compared to a conventional machine.

The proven digital fine finishing generator (D-FS) is also optionally available for the MV-R Series.

Digital FS

Workpiece height

Achieve surface finishes as good as Ra $0.2\,\mu\text{m}$ in the standard version - by using the V350 generator with H-FS technology.



Precision for steps and around corners.



Process Control at its best – Power Master



Getting a grip on radii and corners



Better straightness and shape accuracy

Conventional

- Technology adjustmentIncreased number of cuts
- Angle compensation
- Angle compensation
 High wire spooling rate

posit work



MV-R CONNECT

Digital AE II



The Power Master Control gives the most highest level of process stability – whatever the shape being cut. Stepped workpiece shapes, boreholes and other obstacles to a stable cutting process are identified as soon as they appear and the control adopts cutting and flushing parameters for a safe process and superlative accuracy. On small inner and outer corners and complicated geometries, Corner Master 3 comes to your aid. You merely define your priorities, and optimisation is performed accordingly. With precise control of the electrical discharge position, material is only removed where it needs to be. The patented functions of the Digital AE II improve rough and fine machining and fine finishing – in terms of both precision and machining time.

Reliable process control for higher productivity. 21



Corehold. Intercepting the waste – fully automatically.



MV-R CONNECT

Intercepting the waste - fully automatically







Reducing machining time



During roughing, a bridge is controllably created to hold the waste material – the waste material cannot fall. In this way many features can be rough-machined and, after removal of the waste material, recut – fully automatically and unmanned, overnight and at weekends. Lower costs, higher profits. The number and length of fixing points are easy to set in different ways: directly via a comfortable dialogue menu within the CNC or on external programming systems supporting this function. Standard core connections are replaced by easily removable fixing points, thus reducing the manned time for picking up core parts dramatically. Instead of cutting off the material bridges slowly, the core can be easily removed from the workpiece with slight manual pressure to the core, so the finishing process can start sooner. Remarkable time saving in detail help to reduce overall processing time, contributing to higher process efficiency.

Higher profits thanks to higher efficiency. 23



Dialogue-assisted navigation.

The fast way to the perfect result.



Slim ergonomic manual control box



Multi-touch display with gesture control



An easy start thanks to dialogue guidance



The ergonomically designed, intelligent manual control box unites all the relevant functions for control and set-up in a single unit. The integrated LCD display can be individually configured by the operator. Inclusive of buttons for driving all 8 possible CNC axes. Intuitive operation from the large screen with modern gesture control boosts comfort, while the configurable user interface supports the user by allowing the main functional elements to be freely arranged during daily work. With step-by-step dialogue guidance, less experienced users are piloted through the entire process, from programming through to the start of machining. Checklists make it possible to review all process-relevant settings and machine states so that machining yields the bestpossible results without interruption.





Professional mode -

tailored to your needs.



MV-R CONNECT

Everything at a glance



Work scheduling - at the machine



Help at a keystroke





4	Dielectric Ruid	Update	chir	18	5760	Hours	1.00	
3	Specific Recording	Operator		-			Change	
	Warking Talk	Update		-			1.1	
	Gractining Position	Update	- E2	(8)	101	(*)	100	12
	Wee Colomon Section	. Algorithm		10			1.1	
	Jubrication Clifing	Update					change	
10	Niter Regulator	Update	- P.,	- 92 - L	1410	- W	141	

B Lower Guid C	Update	
0 Lower Guid UD	Update	
1 Rectification Plate	Update	0
2 Lower Roller	Update	0
3 Miscelaneous	Update	

The easy-to-grasp display of all the key machining parameters in configurable form keeps everything under control at all times. Clearly visible at a glance are – if desired – machining status, elapsed times, state of maintenance and other data. Configuration couldn't be simpler. During the preparation of pending machining tasks, support is provided by overviews of the remaining wire, state of filter cartridges and deionisation resin, and other parameters. This way you can prevent outages caused by finite consumables or wear parts and optimise machine running times. The complete machine documents inclusive of maintenance instructions are always available, and the right help is quickly found. Comprehensibility is aided by photos and 3D depiction.

Simply achieve more. 27



If time is of the essence or you want the machines to take some of the work off your shoulders. Set-up often takes too long; from now on, you can save this time.

Highly accurate probing cycles on the sides and corners measure the workpiece precisely. With or without jet stream or even submerged, by means of the cutting wire or with the optional 3D touch probe – just as you wish.









Manual control



3D position measuring – manual or automatic



Intelligent user guidance takes you to the finish. The electrical discharge machine takes you quickly to your goal. Comfortable set-up with the manual control box: standard equipment with Mitsubishi Electric. All essential control functions at hand – wherever you need them. Both are possible. As a user, you decide whether you do set-up classically by hand or the machine automatically defines the position of your workpiece. Using the cutting wire or pick-up coil – the machine takes care of it for you. It only takes the press of a button.

Making my life easier. 29





Job scheduler, inbuilt flexibility.

Manage, pause and resume jobs the easy way.



Integrated job scheduling



Fast and flexible work planning



Pause a job – and resume



Greater flexibility thanks to adaptable job scheduling: with the simple assignment of priorities, you can quickly respond to changing requirements and squeeze in an urgently needed part with ease. Several machining programs can be deposited in the job scheduler and managed there. This is the easy way to add new jobs during machining or change the order of existing machining operations. The new job processing system with priority management makes it possible to amend a machining list without interrupting machining. A machining process is easy to pause even in midflow when urgent jobs have to be processed. The control stores the current state of machining. When the inserted job has been completed, machining can be immediately resumed at the point of interruption. Pushbutton flexibility without programming effort.

"Automation light" installed at the same time. 31





The machine that crunches numbers –

so that you can maximise your profits.

Far-sighted maintenance management

	Initial	setting	Op	eration	History	management	
Noul-	Inspection	Operation	Consumption:	Cost	File management		Beck No.
Parts	ist						
Main Co	onsumption				•	Save Change	Info
Remain	a n 40:22:29 ower Feeser UI Time OHr a	pper Diamond Die	Use Time OHr Lower Diamond Die Use Time OHr	Use Time CHr	Check the 1. Inspector (1) Check state w does n 0 25M use M field St (2) Remo or the 1 Story	e dielectric fluid flit procedures the filee pressure under there the dielectic fluid of overflow If it reaches Pa, replace the filee. Ori subishi original dielectric or er the filter protector, check the usely for damage or leak	13 130 100
Miscella	neous Consump	tion					
Main Te	Time OHr	MT Pinch Roller	Auxiliary Die	Annealing Roller	The fill one fill proce the fill drash atum or dut	er pressure criteria is the r iron materials using. The service life of er will be shodened cally when performing sum materials processing to the use of different.	

Visual process management

	Initial se	etting		0	peratio	m		H	story ma	nagem	ient
AVI .	MAINTNANCE	OPERATION LOG	SU	PLIES		COST		MANEGE	ANT		
event L	og										
Time I	Unit Daily	Weekly M	onthly	16/	08/23					1	Francis dy !
Opera 56	cion Rate	Run Mh 30m 13s 3625%	Sto 30h 19r	0 a151 a006		Alarm 7h 12m 5. 12	23 9%	S 196 2	etup I3m 28s 31.54%		Idie 16h 33m 56s v.zen
		1709-00 04719		110	44.4	•	08/21		/22	19/23	18/06/2420
Proces	s Result List						Detal		Show		Save
Exit Status	Finished Date/Time	Comment	Main L No.	Wire Dia	Wire Mat	Wkpc Mat	Wkpc Thk	Complete Parts	Processing Time	Alarm	Processing Cost
M02	15/08/21 18:01:02	Die 2nd	10	0.2	BS	WC-Co	30		2.21:11	0	¥1,103
M02	16/08/21 14:43:00	Dia 2nd	. 10	0.2	85	WC-Co	30	3	53059	0	¥2,575
Reset	16/08/21 00:13:59	Camp	1	0.2	85	STEEL	60	0	5:25:48	0	¥2,379
Reset	16/08/20 14 29:00	Clamp		0.2	85	STEEL	80	0	1.35:56	0	¥682
	16/08/20 1252:00	Clamp	1	0.2	85	STEEL.	:00	0	2:07:15	0	¥871
Reset					and it	error	- 90	0	2:00:41	0	4831
Rosot Reset	16/08/20 10:40:00	Clamp	1	0.2	85	STOL					
Reset M02	16/08/20 10:40:00 16/08/20 08:29:00	Clamp MIN	1	0.2	85	WC-Co	30		2054.39	1	¥9,257
Reset M02 M02	16/08/20 10:40:00 16/08/20 08:29:00 16/08/19 09:38:00	Clamp MIN Punching finich	5	0.2 0.2 0.2	85 85 85	WC-Co STEEL	30	1	20.54.39	1	¥9,257 ¥5,602
Reset NO2 MO2 MO2	16/08/20 10:40:00 16/08/20 08:29:00 16/08/19 09:38:00 16/08/18 16:54:00	Clamp MIN Punching finich Punching finich	1 5 5 5	02 02 02 02	85 85 85 85	STEEL STEEL	30 10	1	20.54.39 15:20:16 0:22:07	1 3 0	¥9,257 ¥5,602 ¥161

Analysis of operating costs

Rich Ne	File management		numetion	a second second second			
			isumption	Operation Con	nspection	In	NIN
					Consumption	•	Wire
Save Cost Info		07/20/17	Yearly	Veekly Monthly	Gaily	Unit	Time U
0 🗐 🍄	ption cost total	Power Consum			umption Chart	r Consu	Power
		ption(kwh)	Power Consur				
0 [ption cost total	Power Consum option[kWh]	Power Consur	,	umption Chart	r Consu	Power



All the key consumables are monitored online and presented with their anticipated remaining life. This includes display of the remaining life of the wire spool installed in the machine as well as indication of filter pressure and, calculated from this, the probable period until the next filter change. Machine states depicted over time make capacity utilisation easier to grasp and assist forward-looking production planning. This overview is supplemented by a list of completed machining jobs and the associated machine times and unit costs. Given knowledge of unit costs and their inclusion in the machine's own analysis, records of consumption data such as energy consumption, wire consumption and component wear help with cost analysis and the costing of pending machining jobs.





Online service for higher productivity.

Boost your transparency and simply get more out of your machine.

After-sales service online







No compromising on security



Rapid online help to reduce downtime and expenditure on service assignments. Applications support with direct access to the machine control can provide the machine operator with optimum and rapid assistance when faced with difficult tasks. All in the aid of improving production operations. Operating and process data can be retrieved at the control. Available as standard is an export function for all process data, operating states, consumption data and maintenance states as well as alarms. This way the data from several machines can be viewed and evaluated in consolidated form, through to their integration in higher-order production management systems.

Anti-virus protection is ensured as standard by one of the world's leading software systems in security control.



Always right up-to-date. 35





Always up to date –



+ Option



You can control the machine and keep an eye on processes, wherever you are. Intelligent communication takes the pressure out of work. Ideal combined with automation solutions and high process autonomy with the intelligent AT wire threader.

mcAnywhere Service (standard on the MV-R Connect) Rapid help from Mitsubishi Electric experts.



mcAnywhere Control

Comfortable and reliable remote control for your EDM system – powered by TeamViewer.

mcAnywhere Contact+

Any time, any place ... you're always up to date with direct status reports by email. Status reports can be optionally sent by text message – a GSM modem with a suitable driver can be added for this.



Cleaning the tank seal

With the ingenious auto-clean function, your tank seal always stays impeccably clean. This ensures



Quick replacement, long-term savings.



MV-R CONNECT









Simply replace the spool and feed the cutting wire over the feed rollers. Everything ready for work again in 92 seconds.

...without tools or wasted time. Two hands, 32 seconds - and the filter is replaced.



Replace the power feed contact with just one hand and a small gauge - at a speed befitting Formula One.



Straight to the movie: www.mitsubishi-edm.de/filters



Sample calculations Workpiece Punch, steel 1.2379 – 100 mm cutting length Cutting height . . . 60 mm Surface..... Ra 0.28 µm (compared to Ra 0.35 µm for conventional EDM machine) Wire electrode... Brass, 0.20mm

Higher performance: Energy costs reduced by up to 69%



* Assuming production of six punches per working day, electricity price 0.15 euros/kW for 250 working days/year

Greater precision faster

= lower piece costs.







Reduce cost of ion exchange resin









Producing more, less expensively. How it's done.



30.76% more productive capacity



Better result: Wire consumption reduced by up to 46%



	Conventiona		MV-R Connect			32 mir	nutes	faster
				1	2	3	4	Total
Cutting time in minutes								
MV-R Connect, Ra 0.28µm							23	104
Conventional EDM machine	, Ra 0.3	5 µm		80	20	20	16	136

* Assuming production of six punches per working day, bare brass wire (0.20 mm) price 9.60 euros/kg for 250 working days/year

Convention	R Connec						
	MV-			save	EUR ed per	3,300 year*	
		Savir	ngs: 837	7 metres	s per wo	orkpiece	
		1	2	3	4	Total	
Wire consumption in metres							
MV-R Connect, Ra 0.28µm		406	272	167	241	1086	
Conventional EDM machine, Ra 0.3	35 µm	1090	303	303	227	1923	

More output per unit of space. 43







Customised extension.

The intelligent solution.

3D probing



Angle Master Advance II



ERGO-LUX (machine lights)



Mounted on the machine head, activated on command. The intelligent solution.

Tool package



Complete kit for the machining of rotationally symmetrical tools with PCD or CBN cutting edges.

Special wire guide and sequential calculation of the wire set-up point for precision angles.

16/20/25 kg wire station



Accommodates large wire spools with ease. (Standard equipment on the MV4800R Connect) Working conditions that are kind to your eyes – for the sake of users and for the benefit of machining results.

Warning lamp



Machine status is visible from a distance.

From grinding wheels to high-precision cones: a future-proof machine that you can upgrade at any time.



Extend your machine's functions.





Rotary swivel axis



Mini-rotational axis



Rotational machining





A servo-controlled B-axis fully integrated in the machine controls permits wire cutting on a rotating carried workpiece. Separation and multi-sided machining can be performed in a single clamping as well as simultaneously. Machining cones to the highest standards of precision: the rotational/swivel axis integrated in the machine controls. Multi-axis machining to the centre of the workpiece and multi-sided machining in a single clamping, plus the realisation of high-precision conical polygons.



Can be used for reliable indexing and simultaneous machining as well as high-speed rotation (EDM grinding): the servo-controlled rotational machining fully integrated in the machine controls. Discover new production scope!

47 Extra axes: Expand your possibilities - boost your earnings.



Automation has to be flexible.

Reconciling different brands.

Optimum solutions – customised, configured or standardised

The handling systems and robots from different manufacturers can often be seamlessly integrated. Renowned for their dependability and productivity, the EDM machines of the MV-R Series from Mitsubishi Electric are automation-ready. We'd be happy to show you examples that have proven effective in practice and help you to cut costs and boost your productive capacity.

A 100



Handling equipment from different manufacturers – welcome and easily integrated.

Flexible solution: Articulated-arm robot up to 15 kg of Mitsubishi Electric quality.

Automated integration – here with ZK Chameleon.

49 If you want to make money, automate!



Successfully mastered!

The key to success in a wide range of fields.

 $\textbf{Medicine} \, \cdot \, \textbf{Vehicle industry} \cdot \, \textbf{Communications/electrics} \cdot \, \textbf{Aerospace}$











Experience it with your own eyes: www.mitsubishi-edm.de/core





Service. We're there to help you.

You don't like call centres and queuing systems? We don't either. With every Mitsubishi Electric EDM system you buy excellent service as part of the package. Service is performed by our own highly skilled service technicians so that production is kept dependably up and running. Users are assisted over the phone and benefit from the expertise and wealth of experience of Mitsubishi Electric specialists.

Warehousing and logistics



Original Mitsubishi Electric parts





We supply all in-stock products (wear and spare parts) even outside normal business hours, e.g. by courier or collection. Our proximity to Düsseldorf Airport and motorway links enables us to ship parts at high speed. All standard spare parts of the Mitsubishi Electric consumables line are original imports or fabricated in Germany in accordance with the development and design specification. You receive original parts of immaculate quality at attractive prices.





Training. Helping you to stay up to date.

Training



Training centre



Courses, seminars and user workshops

The varied programme covers everything from basic knowledge through to customised training geared precisely to your employees' learning needs. In addition, we also hold regular applications workshops – free of charge to our customers – which always deal with cur-

Users learn skilled operation right at the machine and at specially configured CNC workstations. This way you benefit most from a direct transfer of expertise. Training is available at the facilities of Mitsubishi Electric in Ratingen, Germany. Additionally, training courses are provided by our international partners. Training on our wire-cutting and die-sinking systems takes place at our own technology and training centre in Ratingen. rent topics in theory and practice.

Equipment and instructors

Our skilled instructors introduce you to our EDM systems in theory and practice. The training facilities are appointed with the latest technology, CNC simulators and peripheral equipment.

Certificates

All training participants receive a certificate on completing a course.



MV2400R CONNECT







hine weight	
erator weight	
hine height	

Required minimum dimensions for Door/Gate passageways (w x h)...2022 x 2150 mm



Key data at a glance. 57

10

A MISHACH





MV4800R CONNECT







Key data at a glance. 59



	Action		Low Contraction	Arr	
Machine	MV1200R	MV2400R	MV2400R Z+	MV4800R	
Travel (X/Y/Z) in mm	400/300/220	600/400/310	600/400/425	800/600/310	
Travel (U/V) in mm	120/120 (+/- 60)	150/150 (+/- 75)	150/150 (+/- 75)	150/150 (+/- 75)	
Taper angle (workpiece height) in °/mm	15/200 30/87	15/260 30/110	15/260 30/110	15/260 30/110	
Max. workpiece dimensions (WxDxH) in mm	810x700x215	1050×820×305	1050×820×420	1250 x 1020 x 305	
Max. workpiece weight in kg	500	1500	1500	3000	
Table dimensions (WxD) in mm	640×540	840×640	840×640	1080×780	
Table layout		Hardened 4-side frame table		Hardened 4-side table	
Possible wire diameters in mm		0.1–0.3		0.15–0.3	
Wire spool capacity in kg		10		10/16/20/25	
Automatic wire threader/wire chopper		Yes/	Yes		
Overall dimensions (WxDxH) in mm	2025x2760x2015	2687×3030×2150	2837 x 3452 x 2380	3100×3475×2415	
Machine weight in kg	2700	3500	3650	5600	
Mains voltage	3-phase 400 V/AC ± 10 %, 50/60 Hz, 13 kVA				
Tank capacity in I	550	860	980	1480	
Filter particle size in µm/filter elements		3/	2		
Temperature control	Dielectric cooling unit				
Weight (dry) in kg	Included in machine weight	350	390	450	
Power supply unit		Regenerative tran	sistor pulse type		
Cooling method	Fully sealed/indirect air cooling				
Max. output current in A		50)		
Dimensions (WxDxH) in mm	600×650×1765				
Weight in kg	240				
Control					
Input method	Keyboard, USB flash drive, Ethernet, 19" touchscreen				
Control system	CNC, closed circuit				
Min. command step $(X/Y/Z/U/V)$ in μ m	0.1				
Min. axis resolution in µm	0.05				

Equipment	MV-R Series	Optional hardware	MV-R Series		
Tubular Shaft Drives with linear scales $(X/Y/U/V)$	Yes	Digital fine finishing generator D-FS	Optional (not retrofittable,		
Control M800 with 19" full-touch monitor	Yes		Ontional		
Hand pilot with configurable LCD monitor	Yes	Thin wire specification 0.05 / 0.07 mm	(not retrofittable, not available for		
Automatic vertical front door	Yes		MV2400R Z+ and MV4800R)		
Digital AE II generator	Yes	Wire station for 16 / 20 / 25 kg wire spools	Optional (standard for MV4800R)		
Fine finishing generator H-FS	Yes	Wire station for 50 kg wire spools	Optional		
Hardened 4-side frame table	Yes (MV4800R: hardened 4-side table)	Angle Master Advance II – basic kit incl. aligning device	Optional		
Digital electricity meter / filter pressure sensor	Yes	Angle Master Advance II – Wire guide kit	Optional		
Ethernet/DNC/FTP	Yes	Automatic Renishaw probe	Optional		
Preparation for automation	Yes (not available for MV4800R)	ERGO LUX LED floodlight	Optional		
McAfee AntiVirus embedded	Yes	Tricolour status lamp	Optional		
Operating data output	Yes	Automatic dielectric water refilling	Optional		
3D CamMagic on-board	Yes	Connection to external cooling system	Optional		
Corehold technology	Yes	External signal output with relay board	Optional		
Job scheduler	Yes	Filter switching system	Optional		
Sleep mode	Yes				
		Optional tools			
		mcAnywhere Service	Yes		
		mcAnywhere Control / mcAnywhere Control light	Optional		
		mcAnywhere Contact / mcAnywhere Contact light	Optional / Yes		
		Tool package / automation solutions	Optional		

Power connection: 3-phase 400V/AC, PE, \pm 10%, 50/60 Hz, primary fuse 32A slow

Pneumatic connection: 5–7 kgf/cm³, 500–700 kpa, minimum air flow rate 751/min, 3/8" hose connection

The EDM system should be set up on a suitable hard industrial floor and preferably on a consolidated concrete floor. Any shielding that may be necessary in conformity with the EMC Directive is not included in the equipment supplied by Mitsubishi Electric.

The cooling unit contains fluorinated greenhouse gas R410A. For further information, please refer to the associated operating instructions.



Details can be found in the assembly plan of the machine: www.mitsubishi-edm.de/download





Partners



Fraunhofer





