PROFESSIONAL FILTRATION COOLING WATER

HiFlux Auto-line® filters are specially designed for automatic filtration of cooling water.





About the Auto-line® Automatic filter

Installed at several of the world's largest cooling water treatment plants.

Before installation:

Cleaning manual filters regularly, high maintenance costs, downtime in production.

After installation:

Automatic process, increased productivity, minimal maintenance, no production stops.

Facts for the Auto-line® Automatic filter

HiFlux Auto-line® Filter has been designed as a compact, self-cleaning filter. The sturdy construction of the filter makes it well suited for applications in which operational reliability and dependability are essential.

Accurate filtration down to 35 micrometers [µm].

FEATURES

- Removes unwanted particles
 High operational reliability.
- Continuous flow process Self-cleaning application.
- Ensures the quality
 Increased product quality.
- Eliminates downtime Optimizing earnings.









Did you know?

That 1 Auto-line VLR filter can handle 970 m3/h pr. hour and helps protect heat exchangers to extend the lifetime. At one installation 1 Auto-line VLR filter can exchange 6 manual filters and remove the need for filter bags. Furthermore, the time needed for changing filter bags is completely removed due to the self-cleaning filter construction.

Facts and regulations:

PED ATEX
C€ ISO 9001

HiFlux Filtration A/S Lundagervej 25a 8722 Hedensted

www.hiflux-filtration.com info@hiflux.dk

Tel +45 76 74 16 60 VAT no. dk 13 45 74 76